



Wheel Diameter	50 mm
Width of Tread	25 mm
Hardness of Tread	70 Shore D
Size of Plate	73×73 mm
Plate Hole Centers	58×58 mm
Plate Hole	7 or 8.5 mm
Leveling Extent	10 mm
Offset	36 mm
Overall Height	82 mm
Load Capacity / 1 pcs	250 kg
Load Capacity / 4 pcs	500 kg

- ① 脚轮座(top plate): 碳钢冲压(pressed steel plate)
- ② 脚轮壳(frame): 铝制(al diecasted)
- ③ 手把(handle): ABS resin handle
- ④ 底座(leveling pad): NBR resin cushion
- ⑤ 轮子(wheel): 尼龙6(nylon6)
- ⑥ 表面处理(finish): 喷涂&镀锌
powder coated&zinc galvanized

- ▶ 防静电底座 Variety of cushion available
- ▶ 防静电聚氨酯轮子 Antistatic polyurethane wheels
- ▶ 黑色脚轮壳 Black finish is available



Wheel Diameter	50 mm
Width of Tread	25 mm
Hardness of Tread	70 Shore D
Center Bolt	m12
Bolt Length	35 mm
Leveling Extent	10 mm
Offset	36 mm
Overall Height	82 mm
Load Capacity / 1pcs	250 kg
Load Capacity / 4pcs	500 kg

- ① 脚轮座(top plate): 碳钢冲压(pressed steel plate)
- ② 脚轮壳(frame): 铝制(al diecasted)
- ③ 手把(handle): ABS resin handle
- ④ 底座(leveling pad): NBR resin cushion
- ⑤ 轮子(wheel): 尼龙6(nylon6)
- ⑥ 表面处理(finish): 喷涂&镀锌
powder coated&zinc galvanized

- ▶ 防静电底座 Variety of cushion available
- ▶ 防静电聚氨酯轮子 Antistatic polyurethane wheels
- ▶ 黑色脚轮壳 Black finish is available