



## TECHNICAL DATA

Pump Model	: AGP 35 .
No. of outlets	: One
Output	: 35cc/ stroke
Pump ratio	: 31:1
Dely. pressure	: 186 bar max. at 6 bar air pressure
Operation	: Air Pressure , Single stroke , Air Return.
Reservoir	: Transparent 2 ltrs. Capacity with refilling nipple arrangement.
Level Control	: Visual With Spring loaded follower plate or electrical with low level Switch.
Lubricant	: Any oil and grease upto NLGI-2.
Outlet connection	: 1/4" BSPT/NPT female with 1 way / 2 way check and air bledding assy.
Mounting	: 2 nos. of 10mm dia. bolts.
Accessories	: Control unit with ON & OFF timers 4/2 way sol. valve, & pressure switch.

Central Lubrication Pump model AGP 35 is used in singal line series (Progressive type) System with 1 way check valve and in single line parallel ( Injector type ) system with 2 way check valve.

In later case , care should be taken to ensure pump delivery pressure And output to be more than total volume and operating pressure of Injectors in the circuit.

## MODEL IDENTIFICATION :

	AOP35	LE	B	P	T	2
	AGP35	LV	A	-	-	-
Basic Model Grease /Oil						
Low Level control Visual / electrical						
Solenoid valve coil	A - 24VDC					
	B - 110VAC					
	C - 220VAC					