

**MATERIAL SAFETY DATA SHEET**

<b>SECTION:I - MATERIAL IDENTIFICATION AND USE</b>				
<b>MATERIAL NAME :</b> PURE POLYESTER POWDERS				
<b>MANUFACTURER'S NAME:</b> UNIVERSAL COATING PRODUCTS		<b>SUPPLIER'S NAME:</b> UNIVERSAL COATING PRODUCTS		
<b>Street Address :</b> Gate No.413/1,Plot No.4B, KURULI, CHAKAN		<b>Street Address :</b> Gate No.413/1,Plot No.4B, KURULI, CHAKAN		
<b>City :</b> PUNE I	<b>State :</b> MAHARASHTRA	<b>City :</b> PUNE	<b>State :</b> MAHARASHTRA	
<b>Postal code:</b> 410510	<b>Emergency Tel No.:</b> 9970174035	<b>Postal code:</b> 410501	<b>Emergency Tel No.:</b> 9970174035	
Commercial Name: PURE POLYESTER POWDER		Chemical Name: Polyester TGIC powder coating		
Trade Name and Synonyms: -		Product Use: PAINTING		
<b>SECTION:II – HAZARDOUS INGREDIENTS OF THE MATERIAL</b>				
Hazardous Ingredients	Approx. %	CAS No. U N No.	L D 50 Specify species and route)	L C 50 Specify species and route)
1.BARIUM SULPHATE	10 - 20	7727-43-7	<15000 mg/kg	
2.FILM FORMERS, RESINS, ADDITIVES	50 – 60	NOT ESTABLISHED	--	
3.Caco3 Minerals	0 – 20	12001-26-2	> 16000 mg/Kg	
<b>SECTION:III – PHYSICAL DATA FOR THE MATERIAL</b>				
Physical state: SOLID		Odour and Appearance: NOT APPLICABLE		Odour Threshold(ppm): NOT APPLICABLE
Specific Gravity: 1.6 – 2.0		Vapour Pressure (mm): NOT APPLICABLE		Vapour Density (Air=1): NOT APPLICABLE
Evaporation rate: NOT APPLICABLE		Boiling Point(°C): NOT APPLICABLE		Freezing (°C): NOT APPLICABLE
Solubility in Water: INSOLUBLE		pH : NOT APPLICABLE	Density: (gm / ml) 0.8 – 1.1	
				Co-efficient of Water / Oil distribution: NOT APPLICABLE

<b>SECTION:IV - FIRE AND EXPLOSION HAZARD OF MATERIAL</b>		
Flammability : Yes/No. If yes, under what conditions:		
Yes. 1. IN PRESENCE OF OPEN FLAME, SPARK OR OTHER IGNITION SOURCE 2. UNDER VERY HIGH TEMPERATURES		
<b>Means of Extinction</b> : 1. CARBON DIOXIDE 2. FOAM EXTINGUISHER		
Flash point (°C) NOT APPLICABLE	Upper Explosive Limits (% by volume) 2-3 KG/CUBIC METER	Upper Explosive Limits (% by volume) 30 MG/CUBIC METER
Auto-ignition (°C)Temperature: NOT AVAILABLE	TDG Flammability Classification: NOT AVAILABLE	Hazardous Combustion Products: NOT AVAILABLE
Explosion data: (Sensitivity to Chemical Impact) NOT APPLICABLE	Sensitivity to Static Discharge: RECOMMENDED TO SUITABLY GROUND CONTACT METAL PARTS	
<b>SECTION:V – REACTIVITY DATA</b>		
Chemical Stability: Yes/No (If no, under what conditions)	YES	
Incompatibility with Other Substances: Yes/No	AMINES, BASES, ACIDS, MERCAPTANS	
Reactivity and under what conditions:	NON-REACTIVE UNDER AMBIENT CONDITIONS	
Hazardous Decomposition Products:	INCOMPLETE COMBUSTION CAN YIELD CARBONMONOXIDE AND DIOXIDE, ACIDS AND ALDEHYDES	
Material Name/Identifier:	NOT AVAILABLE	
<b>SECTION:VI – TOXICOLOGICAL PROPERTIES OF MATERIAL</b>		
Route of entry Skin Contact: NON HAZARDOUS	Skin Absorption: NOT APPLICABLE	Eye Contact: IRRITATION
Inhalation Acute: NOT AVAILABLE	Inhalation Chronic: NOT AVAILABLE	Ingestion: NOT AVAILABLE
Effects of Acute Exposure:	NOT AVAILABLE	
Effects of Chronic exposure to material: NOT AVAILABLE		
NOT AVAILABLE		NOT AVAILABLE
Exposure Limits		Irritancy of Material
Sensitization to Material: NOT AVAILABLE	Carcinogenicity, Reproductive Effects, Teratogenicity, Mutagenicity: NOT AVAILABLE	
Synergistic to Material:	NOT APPLICABLE	

<b>SECTION:VII – PREVENTIVE MEASURES</b>		
<b>PERSONAL PROTECTIVE EQUIPMENT</b>		
Gloves: PLASTIC	Respiratory: FACE MASK	Eyes: PROTECTIVE GLASSES
Foot ware: INDUSTRIAL CONDUCTIVE SHOES	Clothing: NORMAL COTTON CLOTHING	Other: NIL
Engineering control (e.g. Ventilation, enclosed process etc.) ⊗please specify) ADEQUATE VENTILATION, DUST CONTROL DURING USE RECOMMENDED		
Leak and Spill Procedure : COLLECT INTO TRAY OR VACCUM CLEAN		
Waste Disposal : INCINERATE OR BURY IN NOTIFIED AREA		
Handling Procedures } NORMAL and Equipment }		
Storage Requirements : AT AMBIENT IN A SHADED AND VENTILATED LOCATION AND AWAY FROM SOURCE OF IGNITION OR FIRE.		
Special Shipping Inforamtion: NIL		
<b>SECTION:VIII – FIRST AID AND MEASURES</b>		
First Aid Measures		
EYE CONTACT : Flush with plenty of water for at least 15 Mints and seek medical attention.		
SKIN CONTACT : Wash with water + soap .		
INGESTION : Seek medical attention.		
INHALATION : Seek medical attention		
Sources used : MATERIAL SAFETY DATA SHEETS – ICMA BOMBAY		
Additional Information : NUISANCE DUST MAY CAUSE CELLULAR RESPONSE IN LUNGS		

**SECTION:IX - DATE OF PREPARATION OF MATERIAL SAFETY DATA SHEET**

Prepared By : TECHNICAL MANAGER  
Phone No. : 9970174035

SMD ENVIROCOATS  
Date : 01/08/2017

**SECTION:X - DISCLAIMER**

Information contained in this material safety data sheet is believed to be reliable and given in good faith, but no representation, guarantee or warranties of any kind are made as to its accuracy, suitability for a particular application or results to be obtained from them. The user of this material decides what safety measures are necessary to safely use this material, either alone or in combination with other materials. Asian Paints Industrial Coatings Limited makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.